

# Controlled Hydrogen Fleet and Infrastructure Demonstration and Validation Project – *Progress Update*

Keith Wipke, Cory Welch, Holly Thomas, Sam Sprik<sup>1</sup>  
Sigmund Gronich, John Garbak, Doug Hooker<sup>2</sup>

March 13, 2006

National Hydrogen Association Meeting

<sup>1</sup>NREL, <sup>2</sup>US Dept. of Energy

## Disclaimer and Government License

This work has been authored by Midwest Research Institute (MRI) under Contract No. DE-AC36-99GO10337 with the U.S. Department of Energy (the “DOE”). The United States Government (the “Government”) retains and the publisher, by accepting the work for publication, acknowledges that the Government retains a non-exclusive, paid-up, irrevocable, worldwide license to publish or reproduce the published form of this work, or allow others to do so, for Government purposes.

Neither MRI, the DOE, the Government, nor any other agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe any privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not constitute or imply its endorsement, recommendation, or favoring by the Government or any agency thereof. The views and opinions of the authors and/or presenters expressed herein do not necessarily state or reflect those of MRI, the DOE, the Government, or any agency thereof.

# Outline

---

- Project Overview and Industry Partners
- Data Collection and Processing
- Analysis Methodology
- First Public Results Now Available:  
Composite Data Products

# Project Objectives and Targets

- Objectives

- Validate H<sub>2</sub> FC Vehicles and Infrastructure in Parallel
- Identify Current Status of Technology and its Evolution
- Re-Focus H<sub>2</sub> Research and Development
- Support Industry Commercialization Decision by 2015



Photo: Shell Hydrogen

Hydrogen and gasoline station, WA DC

## Key Targets

Performance Measure	2009*	2015**
Fuel Cell Stack Durability	2000 hours	5000 hours
Vehicle Range	250+ miles	300+ miles
Hydrogen Cost at Station	\$3/gge	\$2-3/gge

\* To verify progress toward 2015 targets

\*\* Subsequent projects to validate 2015 targets

# Teams are Fielding Four Main\* Types of Vehicles



# Sample Hydrogen Refueling Infrastructure



DTE/BP Power Park,  
Southfield, MI



LAX refueling station



Hydrogen and gasoline station, WA DC Photo:Shell Hydrogen



Chino, CA Photo: H2CarsBiz

# Refueling Stations from All Four Teams Creating Regional Networks



**Additional Planned Stations**  
 Ford & BP (3)  
 DaimlerChrysler & BP (TBD)  
 General Motors & Shell (1)




**Additional Planned Stations**  
 DaimlerChrysler & BP (2)  
 Ford (1)  
 Chevron & Hyundai/Kia (1)



**Additional Planned Stations**  
 General Motors & Shell (2)



**Additional Planned Stations**  
 DaimlerChrysler & BP (2)  
 General Motors & Shell (2)  
 Chevron & Hyundai/Kia (2)




# Data Collection: Overview

Key Vehicle Data	Key Infrastructure Data
Stack Durability	Conversion Method
Fuel Economy (Dyno & On-Road) and Vehicle Range	Production Emissions
Fuel Cell System Efficiency	Maintenance, Safety Events
Maintenance, Safety Events	Hydrogen Purity/Impurities
Top Speed, Accel., Grade	Refueling Events, Rates
Max Pwr & Time at 40C	H <sub>2</sub> Production Cost
Freeze Start Ability (Time, Energy)	Conversion, Compression, Storage and Dispensing Efficiency
Continuous Voltage and Current (or Power) from Fuel Cell Stack, Motor/Generator, Battery & Key Auxiliaries: (Dyno & On-Road)	




# Project Now Well Underway

Current Status of Data Reporting to the Hydrogen Secure Data Center at NREL






# Vehicle Data Analysis: Automated Process from CD/DVD Delivery to Results




Data is delivered to NREL's Hydrogen Secure Data Center (HSDC) on CD/DVDs




Data protected in HSDC for 5 years after data developed under EPACT 2005, Sec. 810




# Analysis Controlled by New NREL-Developed GUI: Fleet Analysis Toolkit (FAT)




# FAT GUI Includes TripView to Dive Deeper and Investigate Individual Trips and Refuelings



# On-Road Voltage Degradation Analysis: Polarization Curve Fitting, Piecewise in Time




# Voltage Degradation Analysis: Individual-Stack Methodology



Created: 28-Feb-2006

# Voltage Degradation Analysis: Multiple-Stack-Average Methodology



# Composite Data Products are Main Output to Public and Hydrogen Community

## A. Critical Program Metrics:

1. Fuel Cell Durability, Actual vs. DOE Targets, All OEM's
2. Vehicle Ranges, Actual vs. DOE Targets, All OEM's
3. H2 Production Cost. Actuals/Projections vs. DOE Targets

## B. Composite Performance Tracking:

### *Vehicles*

4. Reliability (FC System & Powertrain, MTBF)
5. Start Times vs. DOE Target
6. Fuel Economy: Dyno, On-Road
7. Normalized Vehicle Fuel Economy
8. Fuel Cell System Efficiency
9. Safety Incidents - Vehicle Operation
10. Weight % Hydrogen
11. Energy Density of Hydrogen Storage
12. Vehicle Hydrogen Tank Cycle Life

### *Hydrogen Infrastructure*

13. H2 Production Efficiency vs. Process
14. Combined Heat and Power (CHP) Efficiencies
15. H2 Production Cost vs. Process
16. H2 Purity vs. Production Process
17. Hydrogen Impurities - Range for Production Process A
18. Histogram: Refueling Rate
19. Average Maintenance Hours - Scheduled and Unscheduled
20. Safety Incidents - Infrastructure

Highlighted CDPs Have Been Completed and Will Be Presented

## C. High Level Program Progress:

### *Vehicles*

21. Range of Actual Ambient Temperatures During Vehicle Operation – All Vehicle Teams
22. Histogram: # Vehicles vs. Operating Hours to Date
23. Histogram: # Vehicles vs. Miles Traveled to Date
24. Cumulative Vehicle Miles Traveled - All Teams
25. Progression of Low to High Pressure On-board H2 Storage

### *Hydrogen Infrastructure*

26. Cumulative Hydrogen Production – All Teams



# Accomplishment: Baseline Vehicle Chassis Dynamometer Testing Completed by All 4 Teams

- One vehicle per team per geographic region
- 11 vehicles tested using SAE J2572
- Some teams may elect to use test results for EPA certification

DaimlerChrysler/BP



Ford/BP




Chevron/Hyundai-KIA



GM/Shell

# Dynamometer and On-Road Fuel Economy



(1) One data point for each make/model. Combined City/Hwy fuel economy per DRAFT SAEJ2572.


(2) Adjusted combined City/Hwy fuel economy (0.78 x Hwy, 0.9 x City).

(3) Excludes trips < 1 mile. One data point for on-road fleet average of each make/model.

(4) Calculated from on-road fuel cell stack current or mass flow readings.

Created: 16-Feb-2006

# Vehicle Range Based on Dyno Results and Usable H2 Fuel Stored On-Board




Created: 21-Feb-2006

(1) Calculated from combined City/Hwy fuel economy (dyno test) per DRAFT SAE J2572 and usable fuel on board.

# Safety Incidents – Vehicles


Safety Incidents - Vehicle Operation



Created 21-Feb-2006


# Safety Incidents – Infrastructure

Safety Incidents - Infrastructure  
2005 Q2 - Q4




Created 21-Feb-2006

# Vehicle H2 Storage Technologies Include 350 bar, 700 bar, and Liquid H2




Created 16-Feb-2006

# Technical Status of On-Board H2 Storage Technologies Being Validated




Created: 23-Feb-2006

<sup>1</sup>Some near-term targets have been achieved with compressed and liquid tanks. Emphasis is on advanced materials-based technologies.



Created: 23-Feb-2006

<sup>1</sup>Some near-term targets have been achieved with compressed and liquid tanks. Emphasis is on advanced materials-based technologies.




Created: 23-Feb-2006

<sup>1</sup>Emphasis is on advanced materials-based technologies.

Compressed and liquid H2 tanks meet durability and short term weight %, but don't meet long-term weight % or volumetric capacity targets for vehicles

# Hydrogen Purity Sampled from Stations Meets Target Majority of the Time




(1) Includes sampling from both electrolysis and reforming

Created: 21-Feb-2006




# Hydrogen Impurities Sampled from All Stations – Includes On-Site Reformation, Electrolysis, and Delivered H2




Created: 23-Feb-2006

# Actual Vehicle Refueling Rates: Measured by Stations or by Vehicles



Created: 21-Feb-2006


# Range of Ambient Temperature During Vehicle Operation



Created: 16-Feb-2006

# Vehicle Operating Hours and Miles Traveled Distribution


Vehicle Hours: All OEM's Combined through Q4 2005



Data reflect youthful nature of current fleet

Created: 16-Feb-2006


Vehicle Miles: All OEM's Combined through Q4 2005



Created: 28-Feb-2006

# Cumulative Vehicle Miles Traveled and Mass of H2 Produced or Dispensed

Cumulative Vehicle Miles Traveled: All OEMs




Created: 16-Feb-2006

Rate of mileage accumulation increasing as initial fleets approach full deployment

Current deployment of new H2 refueling stations for this project is about 20% complete

Cumulative Hydrogen Produced or Dispensed  
All Teams Combined




Created 21-Feb-2006

# Summary

- First year of the 5-year project completed
  - 59 vehicles now in fleet operation
  - Several new refueling stations opened
  - No major safety problems encountered
- Project has identified current technical status relative to program targets
  - Will track improvements from 2<sup>nd</sup> generation stacks/vehicles introduced mid-way through project
- Future public results will include:
  - FC durability, reliability, efficiency, and start-up times
  - H2 production cost, efficiency, and maintenance

# Questions and Discussion



Contact: Keith Wipke, National Renewable Energy Lab  
303.275.4451 keith\_wipke@nrel.gov