


ECO-IDEA

Hardware-in-the-Loop Test


Jing Wang
Researcher, Grid Automation & Controls Group
jing.wang@nrel.gov

Workshop on Enhanced controls and optimization of
integrated distributed energy applications (ECO-IDEA)
ENERGISE project
November 14, 2019

Data-Enhanced Hierarchical Control Hardware-in-the-Loop Test Setup




Lab Infrastructure



Hardware-in-the-Loop Test

Test scenario: evaluate data-enhanced hierarchical control (DEHC) functionality of coordinated controls to achieve desired voltage profile (0.95–1.05 p. u.).



Test condition: moderate photovoltaic (PV) profile day, from 10:00–14:00.





Hardware-in-the-Loop Test Results

No ADMS control: LTC and cap. bank local control, no ENGOs, PV local control


Baseline



ADMS-centered operation HIL test




Hardware-in-the-Loop Test Results





- The advanced distribution management system (ADMS) sets the tap position of load tap changer (LTC) very low (-5) to reduce the system voltage.
- ADMS gives priority to the LTC to regulate the system voltage before changing commands to capacitor banks.

Hardware-in-the-Loop Test Results

Total PV generation





RTOPF coordinator outputs




- The real-time optimal power flow (RTOPF) algorithms (coordinator and local controllers) converge and work as expected to regulate system voltages.

RTOPF PV local controller outputs



Hardware-in-the-Loop Test Results

Hardware ENGOS



- The edge-of-network grid optimizers (ENGOS) inject reactive power only when the voltage set point is higher than its measured voltage. This is as expected.

Summary of Hardware-in-the-Loop Test

The test demonstrated the following features of the DEHC architecture:

- a. Comprehensive situational awareness
- b. ADMS-centered operation
- c. Synergistic ADMS—grid-edge operation
- d. Fast-regulation capabilities from PV systems.

Help utility partners understand the benefits of adopting hierarchical controls for ADMS-centered operation to collectively manage slow-response legacy devices and fast-response PV inverters and grid-edge devices to maintain grid voltages within safe operating limits with increasing PV penetration.

Thank you

www.nrel.gov

Jing.Wang@nrel.gov

NREL/PR-5D00-75411

This work was authored in part by the National Renewable Energy Laboratory, operated by Alliance for Sustainable Energy, LLC, for the U.S. Department of Energy (DOE) under Contract No. DE-AC36-08GO28308. Funding provided by U.S. Department of Energy Solar Energy Technologies Office. The views expressed in the article do not necessarily represent the views of the DOE or the U.S. Government. The U.S. Government retains and the publisher, by accepting the article for publication, acknowledges that the U.S. Government retains a nonexclusive, paid-up, irrevocable, worldwide license to publish or reproduce the published form of this work, or allow others to do so, for U.S. Government purposes.

