

Paper No: 1570735193




Performance Evaluation of an Advanced Distributed Energy Resource Management Algorithm


Jing Wang, Jeff Simpson, Rui Yang, Bryan Palmintier, Soumya
Tiwari, Yingchen Zhang
National Renewable Energy Laboratory
Jing.Wang@nrel.gov

HIL Evaluation Overview

- Objective: Validate the control and optimization solution against a simulated real-world distribution system in a realistic testing environment
 - Accurate modeling of distribution system, power hardware inverters, communications
 - Co-simulation
 - Grid Optimization algorithm
 - Communication interface
 - PHIL with 6 DER Racks
 - Cap bank controller
 - Software controller interacts with the real-time simulation model and hardware inverters as if the controller were interacting with a real-world system



Schematic Diagram of the HELICS Architecture




Experimental Setup – DER Racks




Experimental Setup – DER Racks

Rack	# Devices	Physical Devices	Total capacity	Simulated PV capacity
PHIL-1	14	(1) 3 kVA PV, (1) 5 kVS PV, (12) 320 VA μ PV	11.84 kVA	23.5 kVA
PHIL-2	14	(1) 3 kVA PV, (1) 5 kVA PV, (12) 320 VA μ PV	11.84 kVA	19 kVA
PHIL-3	14	(1) 3 kVA PV, (1) 5 kVA PV, (12) 320 VA μ PV	11.84 kVA	93.9 kVA
PHIL-4	14	(1) 3 kVA PV, (1) 5 kVA PV, (12) 320 VA μ PV	11.84 kVA	67.6 kVA
PHIL-5	14	(1) 3 kVA PV, (1) 3 kVA PV , (12) 320 VA μ PV	9.84 kVA	119.2 kVA
PHIL-6	14	(1) 3 kVA PV, (1) 3 kVA PV , (12) 320 VA μ PV	9.84 kVA	54 kVA
Total	84	6 PCCs		

Experimental Setup – Each DER Rack/PCC




Hardware setup and connections for one DER rack




PHIL interface algorithm implemented in OPAL-RT

Experimental Setup – Capacitor Bank Controller



OPAL-RT

Beckwith Cap Bank
Controller



Controller to be tested

Experimental Validation – Voltage Regulation

– Distribution feeder from Hawaiian Electric Company




- Over 2,000 nodes
- 211 loads and 211 PVs (6 PCCs with hardware PV inverters and 205 simulated)
- 50% PV penetration

– Testing details

- Simulation time 12:00-14:00 2-hour run at high solar irradiance

– Testing Scenarios


- Smart Inverter – Volt/Var
- 100% PV being controlled
- 30% PV being controlled





Experiment Results

Real-time implementation details

- Var Priority
- Triggered every 1 s with simulation time step 5 ms
- In total 211 PVs
- Add a deadband (0.005 p.u.) for the two slopes (0.95-0.97) and (1.03-1.05)



Results of system voltages with three scenarios





Experiment Results



Results of Total PV measurements

PV curtailment:

- 0.08% for volt-var
- 0.4% for 100% PV
- 0.24% for 30% PV




Results of one selected simulated PV










PHIL Experiment Results of 30% PV Being Controlled

Performance of State Estimation and OMOO




Mu 30% of PV active




PHIL evaluation
of three DER
Racks (#1-#3)

PHIL Experiment Results of 30% PV Being Controlled

PHIL evaluation of another three DER Racks (#4-#6)



Results of capacitor bank controller



Conclusions

- Successful Power-hardware-in-the-loop (PHIL) testing with GO-Solar platform
 - 84 hardware DER inverters
 - standard communication protocols
 - real responses of hardware inverters
 - stability and dynamics of the GO-Solar platform
- Evaluated voltage regulation performance of the GO-Solar platform in real-time simulation
- HIL captures key real-world aspects and forced us to refine the approaches taken for GO-Solar that were not seen with the artificially tight data coupling from single feeder simulation.
- Results: Once tuned, GO-Solar Platform performs better than the smart inverter volt-var:
 - fewer voltage violations
 - reduced system voltages and improved energy savings (CVR)
 - precise voltage regulation, etc.

NREL/PR-5D00-81288

This work was authored by the National Renewable Energy Laboratory, operated by Alliance for Sustainable Energy, LLC, for the U.S. Department of Energy (DOE) under Contract No. DE-AC36-08GO28308. Funding provided by the U.S Department of Energy's Office of Energy Efficiency and Renewable Energy (EERE) under the Solar Energy Technologies Office (SETO). The views expressed in the article do not necessarily represent the views of the DOE or the U.S. Government. The U.S. Government retains and the publisher, by accepting the article for publication, acknowledges that the U.S. Government retains a nonexclusive, paid-up, irrevocable, worldwide license to publish or reproduce the published form of this work, or allow others to do so, for U.S. Government purposes.