

Impact of Tree Age and Anatomical Fraction on Forest Residue **Pyrolysis and Hydrotreating**

Daniel Carpenter¹, Jordan Klinger², Huamin Wang³, Kristiina Iisa¹, Jim Parks⁴, Gavin Wiggins⁴, Brennan Pecha¹,

1National Renewable Energy Laboratory, 2Idaho National Laboratory, 3Pacific Northwest National Laboratory, 4Oak Ridge National Laboratory, 5Argonne National Laboratory


Matt Wiatrowski¹, Hao Cai⁵, Longwen Ou⁵

Introduction

&OAK RIDGE

Utilization of cost-advantaged biomass and waste resources to produce clean, domestic biofuels will be a key factor in decarbonizing transportation in the United States. This study investigates how the distribution of anatomical fractions (stem wood, bark, needles, branches) from loblolly pine trees of different ages impacts pyrolysis and hydrotreating processes, including product composition, carbon efficiency, economics, and sustainability. Commercially sourced 13- and 23-year-old loblolly pine residues were chosen to represent available resources; whole tree thinnings, and tops and branches from merchantable timber, respectively. Fast pyrolysis experiments were carried out on the whole samples, separated anatomical fractions, and whole samples that were air-classified to

Pacific Northwest




remove loose bark, needs, and soil contaminants. Select samples were processed to hydrocarbon blendstocks, and technoeconomic and life cycle analyses were conducted for the end-to-end

Feedstock Analysis



■ Total liquids ■ Condensables ■ Light gases ■ Water vapor ■ Char ● C to Oi




Feedstock Ash: 0.3-3.9 wt%

Mass balance: 98 ±2%

Oil Yield: 53-72% (d/b)

Carbon to Oil 29-64%

Technoeconomic and Life Cycle Analysis




Conceptual design case considered here1: Biofuel production via catalytic fast pyrolysis (CFP). CFP yields were extrapolated from data presented here based on

Economics for both feedstocks are similar Residues were the most economical option despite a slightly higher conversion cost, driven by lower supply costs (harvesting costs are allocated to merchantable wood products).



\$27.34







The GHG emissions are dominated by the displacement credits for the co-products (2butanone, acetone, and excess electricity).

Methods

- · Feedstock: Commercially sourced Loblolly pine
- "Residues" = 23 yr. tops and branches
- "Thinnings" = 13 yr. whole trees
- · Anatomical fractions were hand separated
- · Residues were also air classified at two fan speeds
- · Fast pyrolysis: 2" ID fluidized bed reactor (2FBR)
- Temperature: 500 °C
- · Feed rate: 0.3 kg/h
- · Product collection: fractional condensation
- · Hydroprocessing: 40 mL/h fixed trickle bed reactor
- · Two-step process
- Stabilization: Ru/TiO₂, 140 °C, 1800 psi, LHSV 0.23 h⁻¹ in H₂
- Hydrotreating: sulfided NiMo/Al₂O₃, 400 °C, 1800 psi, LHSV 0.22 h-1 in H2 + DTBDS (sufiding agent)

Fast pyrolysis product distributions, ranked by total liquid yield. Condensables were measured by online GC/MS-PolyArc FID. All oils except from bark were single phase.





Quantitative GC/MS-FID analysis of pyrolysis oils, ranked by % mass accounted by calibration of 36 compounds (https://www.nrel.gov/docs/fy16osti/65889.pdf).

Fast Pyrolysis

	Hydroprocessing					Carbon Distribution		
							Light Gas: 0.12	
	Stem	Whole	Stem	Residues	p 000	Materials 1/88	Bio-est: 0.67	Light Gentlet: 0.25
	13-yr	(13-yr)	(23-yr)	(23-yr)	stem wood			
Hydrotreating performance					50			Hydrocarbon Products: 0.42
Hydrotreated oil yield, g/g bio-oil,	0.419	0.416	0.401	-	13-yr			
dry basis	0.545	0.530	0.637			Charl 0.1		
	0.645	0.629		-			Materije: 0.03	
H ₂ consumption, g/g bio-oil, dry basis 0.058 0.052 0.065 - Hydrotreated oil composition							ight Gas: 0.12	
C. wt.%. dry basis	86.4	86.7	87.1	86.7				
O, wt.%, dry basis	<0.1	<0.1	<0.1	<0.1	8	Bio-elli 0.62 Dioresca: 1.00		Light Cos/Bal.: 0.22
S, ppm, by ICP	18	8	10	10	stem wood		Bio-eff: 0.62	
Gasoline (IBP-150), wt.%, sim-dist	39.5	43.0	43.9	39.8	tem			Hudineschen Products: 8.40
Diesel (150-350), wt.%, sim-dist	48.5	46.8	45.4	49.6	s s		Hydrocarbon Products: 8.48	
Jet (150-250), wt.%, sim-dist	26.7	26.1	24.3	27.4	23-yr s			
Heavies (>350), wt.%, sim-dist	12.0	10.3	10.7	10.8] "		Chor: 0.21	
							Datable: 0.03	

Conclusions

- · Higher bio-oil yield was generally correlated with total volatiles, hydrogen, oxygen, glucan, and mannan
- · Lower bio-oil yield was correlated with fixed carbon, nitrogen, sulfur, and
- Air classification reduced ash, extractives, and sulfur, resulting in an increase in yield and GC-detectable compounds
- · Sulfur contained in needles appears to disproportionally partition to the oil phase compared to the other fractions
- · Hydrotreating yields and distribution of hydrocarbon fuel products were comparable for thinnings and residues of different ages
- The minimum fuel selling price is similar for thinnings and residues
- · GHG emissions for thinning and residues can achieve >80% reduction vs. fossil-derived equivalents, a large driver being co-product credits



Acknowledgements

The authors wish to especially thank laboratory staff who persevered through pandemic restrictions to carry out experiments and collect the data presented here – NREL: Scott Palmer, Kelly Orton, Carson Pierce, Calvin Mukarakate, Earl Christensen, Rianna Martinez, Alex Rein, Jeremy Bussard, Andy Larson, and Joel Miscall; INL: Jordan Klinger, Tiasha Bhattacharjee, Susan Carilli, Brad Thomas, and Kastli Schaller; PNNL: Suh-Jane Lee and Daniel M. Santosa.



