
















PeleLMeX: an AMR Low Mach Number Reactive Flow Simulation Code without level sub-cycling

Lucas Esclapez ¹, Marc Day ¹, John Bell ², Anne Felden ², Candace Gilet⁴, Ray Grout ¹, Marc Henry de Frahan ¹, Emmanuel Motheau ², Andrew Nonaka ², Landon Owen³, Bruce Perry ¹, Jon Rood ¹, Nicolas Wimer ¹, and Weiqun Zhang ²

¹ High Performance Algorithms and Complex Fluids, National Renewable Energy Laboratory, USA ² Center for Computational Sciences and Engineering, Lawrence Berkeley National Laboratory, USA ³ Sandia National Laboratory, USA ⁴ Independent Researcher, USA

DOI: [10.21105/joss.05450](https://doi.org/10.21105/joss.05450)

Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: [Kyle Niemeyer](#) 

Reviewers:

- [@mameehan5](#)
- [@zzz105](#)
- [@muellerm-pu](#)

Submitted: 14 February 2023

Published: 31 October 2023

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

PeleLMeX simulates chemically reacting low Mach number flows with block-structured adaptive mesh refinement (AMR). The code is built upon the AMReX ([Zhang et al., 2019](#)) library, which provides the underlying data structures and tools to manage and operate on them across massively parallel computing architectures. PeleLMeX algorithmic features are inherited from its predecessor PeleLM ([PeleLM Team, 2022](#)) but key improvements allow representation of more complex physical processes. Together with its compressible flow counterpart PeleC ([Henry de Frahan et al., 2023](#)), the thermo-chemistry library PelePhysics and the multi-physics library PeleMP, it forms the Pele suite of open-source reactive flow simulation codes.

PeleLMeX uses a finite volume approach to solve the multi-species reacting Navier-Stokes equations in their low Mach number limit ([Day & Bell, 2000](#)), where the characteristic fluid velocity is small compared to the speed of sound, and the effect of acoustic wave propagation is unimportant to the overall dynamics of the system. Accordingly, acoustic wave propagation can be mathematically removed from the equations of motion, allowing for a numerical time step based on an advective CFL condition. This low Mach number limit mathematically translates into a constraint on the divergence of the velocity field ([Majda & Sethian, 1984](#)). The momentum equation is then solved for using a predictor/corrector method initially developed for incompressible flows ([Almgren et al., 1998](#)) and later extended to reactive, variable-density flows ([Pember et al., 1998](#)). In the low Mach framework, the thermodynamic pressure is uniform in space but can evolve in time when simulating closed domains with chemical reactions and additional mass injections ([Nonaka et al., 2018](#)). PeleLMeX uses an iterative Spectral Deferred Correction (SDC) time advancement scheme ([Nonaka et al., 2012, 2018](#)) to ensure a tight coupling of the fast diffusion/reaction and the comparatively slow advection, while iteratively enforcing the low Mach number constraint. Advection terms are treated explicitly using second-order Godunov schemes ([AMReX-Hydro Team, 2022](#)), diffusion terms are treated semi-implicitly with a Crank-Nicholson scheme and the often stiffer reaction term is obtained using a fully implicit Backward Differentiation Formula scheme (specifically, the CVODE integrator ([Balos et al., 2021](#)) of the Sundials suite ([Gardner et al., 2022](#); [Hindmarsh et al., 2005](#))). The solution of the linear systems arising in the implicit diffusion and velocity projections are handled using AMReX's native geometric multigrid (GMG) solver, but can also be transferred to HYPRE ([Falgout & Yang, 2002](#)) if GMG fails. In contrast with PeleLM, PeleLMeX relies on a non-subcycling approach to advance the numerical solution on an AMR hierarchy, where all the levels are advanced together using the same time step, the size of which is prescribed by a CFL condition across all the levels. This distinctive feature drove the development of PeleLMeX as it enables extending the closed chamber algorithm described in

(Nonaka et al., 2018) to an AMR hierarchy and incorporating more complex physical processes such as flame/plasma interactions (Esclapez et al., 2020).

In addition, PeleLMeX uses an Embedded Boundary (EB) approach to represent complex geometries: an arbitrary surface can be intersected with the Cartesian matrix of uniform cells, and the numerical stencils are modified near cells that are cut by the EB. Redistribution schemes (Giuliani et al., 2022) are then used for the explicit advection and diffusion updates in order to alleviate the constraint associated with small cut cells. Through its dependency to the multi-physics library PeleMP, PeleLMeX also inherits the ability to include Lagrangian sprays as well as soot and radiation models.

PeleLMeX is written in C++ and is built upon the AMReX (Zhang et al., 2019) library from which it inherits its parallel paradigm. It uses a MPI+X approach where MPI is used to distribute AMR grid patches across CPU ranks and each grid can be further divided into logical tiles spread across threads using OpenMP for multi-core CPU machines, or spread across GPU threads using CUDA/HIP/SYCL on GPU-accelerated machines.

Statement of Need

Several software tools for reactive flow simulations can be found online (often with limited access), including unstructured body-fitted solvers based on OpenFOAM (Hassanally et al., 2018), the structured solver NGA2 (NGA2 Team, 2023), and the Sierra/Fuego solver (Domino et al., 2003). In contrast with the aforementioned solvers, PeleLMeX is fully publicly available and documented. Its unique features consist in combining an AMR approach with a low Mach number formulation to achieve high performances from a small desktop station to the world's largest supercomputer. Recent code developments focused on enabling massively parallel simulations at scale on high-performance accelerated computer architectures to tackle the challenging requirements of fundamental and applied combustion research, as well as extending the solver modeling capabilities by including Large Eddy Simulation (LES) closure models and support for data-driven combustion models (Perry et al., 2022).

PeleLMeX is intended for students, researchers and engineers interested in understanding complex combustion processes by performing high fidelity simulations. Although it can be used to study laminar flames, its distinctive features make it particularly attractive for studying the fine scale flame/turbulence interactions in combustion applications where AMR is necessary to tackle the large scale separation and the computational resources available on the latest heterogeneous exascale platform can be leveraged. In order to achieve energy, transport and industrial decarbonization, fuel-flexible combustion devices must be designed and deployed to accommodate hydrogen, ammonia and a wide range of biofuels. In this context, PeleLMeX can prove a valuable tool to study alternative fuels combustion characteristics, flame dynamics or pollutant formation mechanisms, both in academic idealized cases (Howarth et al., 2023) as well as in device scale simulations (Appukuttan et al., 2023).

Acknowledgments

This research was supported by the Exascale Computing Project (ECP), Project Number: 17-SC-20-SC, a collaborative effort of two DOE organizations – the Office of Science and the National Nuclear Security Administration – responsible for the planning and preparation of a capable exascale ecosystem – including software, applications, hardware, advanced system engineering, and early testbed platforms – to support the nation's exascale computing imperative. This research used resources of the Oak Ridge Leadership Computing Facility, which is a DOE Office of Science User Facility supported under Contract DE-AC05-00OR22725 and computing resources sponsored by the Department of Energy's Office of Energy Efficiency and Renewable Energy and located at the National Renewable Energy Laboratory. This work was authored in part by the National Renewable Energy Laboratory, operated by Alliance for Sustainable Energy,

LLC, for the U.S. Department of Energy (DOE) under Contract No. DE-AC36-08GO28308. The views expressed in the article do not necessarily represent the views of the DOE or the U.S. Government.

References

- Almgren, A. S., Bell, J. B., Colella, P., Howell, L. H., & Welcome, M. L. (1998). A conservative adaptive projection method for the variable density incompressible Navier–Stokes equations. *Journal of Computational Physics*, 142(1), 1–46. <https://doi.org/10.1006/jcph.1998.5890>
- AMReX-Hydro Team. (2022). AMReX-hydro: AMReX-based hydrodynamic routines. In *GitHub repository*. GitHub. <https://github.com/AMReX-Codes/AMReX-Hydro>
- Appukkuttan, S. N., Perry, B., Yellapantula, S., Esclapez, L., Sitaraman, H., & Day, M. (2023). Simulations of fuel-air mixing in a 7 element lean direct injection (LDI) aviation combustor. *Proceedings of the 13th U.S. National Combustion Meeting*.
- Balos, C. J., Gardner, D. J., Woodward, C. S., & Reynolds, D. R. (2021). Enabling GPU accelerated computing in the SUNDIALS time integration library. *Parallel Computing*, 108, 102836. <https://doi.org/10.1016/j.parco.2021.102836>
- Day, M., & Bell, J. (2000). Numerical simulation of laminar reacting flows with complex chemistry. *Combustion Theory and Modeling*, 4(4), 535–556. <https://doi.org/10.1088/1364-7830/4/4/309>
- Domino, S., Moen, C., Burns, S., & Evans, G. (2003). SIERRA/Fuego: A multi-mechanics fire environment simulation tool. *41st Aerospace Sciences Meeting and Exhibit*, 149. <https://doi.org/10.2514/6.2003-149>
- Esclapez, L., Ricchiuti, V., Bell, J. B., & Day, M. S. (2020). A spectral deferred correction strategy for low Mach number reacting flows subject to electric fields. *Combustion Theory and Modelling*, 24(2), 194–220. <https://doi.org/10.1080/13647830.2019.1668060>
- Falgout, R. D., & Yang, U. M. (2002). Hypre: A library of high performance preconditioners. In *Lecture notes in computer science* (Vol. 2331, pp. 632–641). Springer. https://doi.org/10.1007/3-540-47789-6_66
- Gardner, D. J., Reynolds, D. R., Woodward, C. S., & Balos, C. J. (2022). Enabling new flexibility in the SUNDIALS suite of nonlinear and differential/algebraic equation solvers. *ACM Transactions on Mathematical Software (TOMS)*, 48(3). <https://doi.org/10.1145/3539801>
- Giuliani, A., Almgren, A. S., Bell, J. B., Berger, M. J., Frahan, M. H. de, & Rangarajan, D. (2022). A weighted state redistribution algorithm for embedded boundary grids. *Journal of Computational Physics*, 464, 111305. <https://doi.org/10.1016/j.jcp.2022.111305>
- Hassanally, M., Koo, H., Lietz, C. F., Chong, S. T., & Raman, V. (2018). A minimally-dissipative low-Mach number solver for complex reacting flows in OpenFOAM. *Computers & Fluids*, 162, 11–25. <https://doi.org/10.1016/j.compfluid.2017.11.020>
- Henry de Frahan, M. T., Rood, J. S., Day, M. S., Sitaraman, H., Yellapantula, S., Perry, B. A., Grout, R. W., Almgren, A., Zhang, W., Bell, J. B., & Chen, J. H. (2023). PeleC: An adaptive mesh refinement solver for compressible reacting flows. *The International Journal of High Performance Computing Applications*, 37(2), 115–131. <https://doi.org/10.1177/10943420221121151>
- Hindmarsh, A. C., Brown, P. N., Grant, K. E., Lee, S. L., Serban, R., Shumaker, D. E., & Woodward, C. S. (2005). SUNDIALS: Suite of nonlinear and differential/algebraic equation solvers. *ACM Transactions on Mathematical Software*, 31(3), 363–396. <https://doi.org/10.1145/1089014.1089020>

- Howarth, T., Hunt, E., & Aspden, A. (2023). Thermodiffusively-unstable lean premixed hydrogen flames: Phenomenology, empirical modelling, and thermal leading points. *Combustion and Flame*, 253, 112811. <https://doi.org/10.1016/j.combustflame.2023.112811>
- Majda, A., & Sethian, J. (1984). The derivation and numerical solution of the equations for zero mach number combustion. *Combustion Science and Technology*, 3(42), 185–205. <https://doi.org/10.1080/00102208508960376>
- NGA2 Team. (2023). NGA2: Object-oriented multi-mesh version of the classic reacting turbulent multiphase flow solver. In *GitHub repository*. GitHub. <https://github.com/desjardi/NGA2>
- Nonaka, A., Bell, J., & Day, M. (2018). A conservative, thermodynamically consistent numerical approach for low Mach number combustion. I. Single-level integration. *Combustion Theory and Modeling*, 1(22), 156–184. <https://doi.org/10.1080/13647830.2017.1390610>
- Nonaka, A., Bell, J., Day, M., Gilet, C., Almgren, A., & Minion, M. (2012). A deferred correction coupling strategy for low Mach number flow with complex chemistry. *Combustion Theory and Modeling*, 6(16), 1053–1088. <https://doi.org/10.1080/13647830.2012.701019>
- PeleLM Team. (2022). PeleLM. In *GitHub repository*. GitHub. <https://github.com/AMReX-Combustion/PeleLM>
- Pember, R. B., Howell, L. H., Bell, J. B., Colella, P., Crutchfield, W. Y., Fiveland, W., & Jessee, J. (1998). An adaptive projection method for unsteady, low-Mach number combustion. *Combustion Science and Technology*, 140(1-6), 123–168. <https://doi.org/10.1080/00102209808915770>
- Perry, B. A., Frahan, M. T. H. de, & Yellapantula, S. (2022). Co-optimized machine-learned manifold models for large eddy simulation of turbulent combustion. *Combustion and Flame*, 244, 112286. <https://doi.org/10.1016/j.combustflame.2022.112286>
- Zhang, W., Almgren, A., Beckner, V., Bell, J., Blaschke, J., Chan, C., Day, M., Friesen, B., Gott, K., Graves, D., Katz, M., Myers, A., Nguyen, T., Nonaka, A., Rosso, M., Williams, S., & Zingale, M. (2019). AMReX: A framework for block-structured adaptive mesh refinement. *Journal of Open Source Software*, 4(37), 1370. <https://doi.org/10.21105/joss.01370>